


1

2


3

4


5




5 ROOF-MOUNTED CONDENSER DETAIL
M2.1 NOT TO SCALE



6 REFRIGERANT PIPING ROOF PENETRATION
M2.1 NOT TO SCALE




7 UL-555 DYMANIC FIRE DAMPER DETAIL
M2.1 NOT TO SCALE




- DETAIL A-A
- MECHANICAL SUBCONTRACTOR SHALL FURNISH ROOF OPENING SIZES & LOCATIONS, FOR STRUCTURAL SUPPORT FRAMING BY GENERAL CONTRACTOR.
 - THIS CURB DETAIL WILL ALLOW THE UNIT TO SLOPE WITH THE SLOPE OF THE ROOF PITCH. THIS DETAIL CAN ONLY BE USED (A) IF THE CONDENSATE DRAIN PAN OUTLET IS ON THE LOW SIDE OF THE UNIT, OR (B) IF THE CONDENSATE DRAIN PAN IS NOT AFFECTED BY SLOPE. THIS DETAIL CAN NOT BE USED IF THE CONDENSATE DRAIN CONNECTION IS ON THE HIGH SIDE OF THE UNIT.
 - COORDINATE THIS DETAIL WITH ARCHITECTURAL APPLICATIONS FOR THE ROOF.

2 ROOFTOP UNIT CURB DETAIL
M2.1 NOT TO SCALE




5 ROOFTOP UNIT DETAIL
M2.1 NOT TO SCALE



- DUCT FABRICATION NOTES:
- DUCTS SHALL BE FABRICATED & INSTALLED PER THE LATEST EDITION OF SMACNA DUCT CONSTRUCTION STANDARDS.
 - ALTERNATE INTERPRETATIONS OF SMACNA DUCT MATERIAL, HANGERS AND REINFORCEMENTS ARE SUBJECT TO ENGINEER APPROVAL, AND REQUIRE SEPARATE SUBMITTAL OF THE ALTERNATES.
 - FLEXIBLE DUCT CONNECTORS SHALL BE PROVIDED WHERE SHOWN ON THE PLAN.
 - SUPPLY AIR DROPS FROM ROOFTOP UNITS SHALL TRANSITION FROM THE UNIT OPENING SIZE TO MITERED ELBOWS, WITH SIZES AS SHOWN ON THE PLAN. IF TWO SUPPLY AIR DUCT RUNS ARE AT THE UNIT, THEN TWO SEPERATE DROPS & ELBOWS SHALL BE PROVIDED.
 - RETURN AIR DROPS FROM THE ROOFTOP UNITS SHALL BE FULL SIZE OF THE UNIT OPENING. OFFSETS SHALL NOT REDUCE THE FREE AREA, AND SHALL NOT EXCEED 30". A RADIUS HEEL HEEL SHALL BE PROVIDED ON 30" OFFSETS. SMALLER OFFSETS SHALL BE MITERED AT BOTH THE HEEL & THROAT.
 - TRANSITIONS SHALL NOT EXCEED 1:3 RATIO (4" TRANSITION PER FOOT SINGLE SIDED TRANSITION, AND 8" PER FOOT DOUBLE SIDED TRANSITION).
 - INSULATION SHALL BE NFPA 90 APPROVED, WITH MINIMUM R-VALUE OF 6.0. WRAP INSULATION SHALL BE 2" THICK (MINIMUM R-6) WITH ALUMINUM FOIL FACING.
 - RECTANGULAR BRANCH CONNECTIONS SHALL BE 45° ENTRY TYPE PER SMACNA FIGURE 2-6.
 - ROUND DUCT CONNECTIONS SHALL BE WITH "CROWN PRODUCTS COMPANY" 624 OR 624-FL FITTINGS, DAMPER AND HANDLE. SPRAY PAINT LOCATIONS OF HANDLES.
 - FLEXIBLE DUCT SHALL INCLUDE AN INNER POLYETHYLENE LINER, A SPRING HELIX, 1-1/4" BLANKET INSULATION (R-6.0), A FOIL OUTER VAPOR BARRIER, AND BE UL-181 APPROVED.
 - ALL TAPE SHALL BE SMACNA APPROVED.
 - SEAL ALL SUPPLY, RETURN & OUTSIDE AIR DUCT JOINTS WITH DUCT SEALER; SEAL ALL INSULATION JOISTS WITH GLASS FABRIC AND MASTIC.

1 CONCEALED DUCTWORK DETAIL
M2.1 NOT TO SCALE



2 VERTICAL AIR HANDLING UNIT DETAIL
M2.1 NOT TO SCALE

SCOPO
design group, LLC
Architecture - Planning - Interiors
1930 San Marco Blvd., Suite 203
Jacksonville, Florida 32207
T 904 253 3902 F 904 253 3906
www.scopodesigngroup.com
AA26001292

PROJECT ENGINEER
W. MICHAEL GREGORY, PE
FLORIDA PE NO. 46607

Gregory Engineering, Inc.
innovative design solutions for engineered building systems
4567 Deep River Place
Jacksonville, FL 32224
W. Michael Gregory, PE # 46607
Cert. of Authorization # 28163

PROJECT TEAM
LANDLORD
PEARL PLAZA PARTNERS, LLC
TENANT
COMMUNITY REHABILITATION RESOURCES
ARCHITECT
SCOPO DESIGN GROUP, LLC
904-253-3902
STRUCTURAL ENGINEER
LATITUDE 30 ENGINEERING
904-247-1855
MECHANICAL ENGINEER
GREGORY ENGINEERING, INC.
904-714-5118
ELECTRICAL ENGINEER
SHAFFER ENGINEERING GROUP, LLC
904-239-3621

DATE	ISSUE
05 OCT 2009	PERMIT

TENANT IMPROVEMENTS FOR
CRC INSTITUTE GREEN TRAINING CENTER
PEARL PLAZA SHOPPING CENTER, SUITE 08
5808 NORTH PEARL PLAZA
JACKSONVILLE, FLORIDA 32208
MECHANICAL DETAILS

PROJECT NO:	09088
DRAWN BY:	WMG
CHECKED BY:	WMG
SHEET NO:	

M2.1
SHEET